

product type designation



CP 443-1 RNA

Communications processor CP 443-1 RNA; 1x 10/100 Mbit/s RJ45 port; ISO; S7, H-communic., open comm. (send/receive) S7 routing; 2x 100 Mbit/s RJ45 port: PRP; ISO; ISO-on-TCP; TCP; UDP S7, H-communic., open comm. (send/receive) S7 routing; time synchronization; IP access Control List; Web diagnostics; SNMPV1.

transfer rate	
transfer rate	
<ul style="list-style-type: none"> at the 1st interface 	10 ... 100 Mbit/s
<ul style="list-style-type: none"> at the 2nd interface 	100 Mbit/s
interfaces	
number of interfaces / according to Industrial Ethernet	3
number of electrical connections	
<ul style="list-style-type: none"> at the 1st interface / according to Industrial Ethernet 	1
<ul style="list-style-type: none"> at the 2nd interface / according to Industrial Ethernet 	2
type of electrical connection	
<ul style="list-style-type: none"> at the 1st interface / according to Industrial Ethernet 	RJ45 port
<ul style="list-style-type: none"> at the 2nd interface / according to Industrial Ethernet 	RJ45 port
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> at 5 V 	5 %
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 5 V / typical 	1.8 A
power loss [W]	9 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-400 single width
width	25 mm
height	290 mm
depth	210 mm
net weight	0.7 kg
product features, product functions, product components / general	
number of units	
<ul style="list-style-type: none"> per CPU / maximum 	14
performance data / open communication	

number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	64
data volume	
<ul style="list-style-type: none"> as user data per ISO connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per TCP connection / for open communication / by means of SEND/RECEIVE blocks / maximum 	8 Kibyte
<ul style="list-style-type: none"> as user data per UDP connection / for open IE communication / by means of SEND/RECEIVE blocks / maximum 	2 Kibyte
number of possible connections / for open communication	
<ul style="list-style-type: none"> by means of T blocks / maximum 	64
data volume	
<ul style="list-style-type: none"> as user data per ISO on TCP connection / for open communication / by means of T blocks / maximum 	1452 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
<ul style="list-style-type: none"> maximum 	128; when using several CPUs
<ul style="list-style-type: none"> with PG connections / maximum 	2
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	128
product functions / management, configuration, engineering	
protocol / is supported	
<ul style="list-style-type: none"> SNMP v1 	Yes
<ul style="list-style-type: none"> DCP 	Yes
configuration software	
<ul style="list-style-type: none"> required 	STEP 7 V5.5 SP2 + HSP or higher
product function / is supported / identification link	Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes
product functions / redundancy	
product function	
<ul style="list-style-type: none"> ring redundancy 	No
<ul style="list-style-type: none"> redundancy manager 	No
<ul style="list-style-type: none"> Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes
<ul style="list-style-type: none"> High-availability Seamless Redundancy (HSR) and Parallel Redundancy Protocol (PRP) coupling 	No
protocol / is supported / Media Redundancy Protocol (MRP)	No
product functions / security	
product function	
<ul style="list-style-type: none"> ACL - IP-based 	Yes
<ul style="list-style-type: none"> ACL - IP-based for PLC/routing 	Yes
<ul style="list-style-type: none"> switch-off of non-required services 	Yes
<ul style="list-style-type: none"> blocking of communication via physical ports 	Yes
<ul style="list-style-type: none"> log file for unauthorized access 	No
product functions / time	
product function / SICLOCK support	Yes
product function / pass on time synchronization	Yes
protocol / is supported	
<ul style="list-style-type: none"> NTP 	Yes
<ul style="list-style-type: none"> NTP (secure) 	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8
<ul style="list-style-type: none"> as marking 	Ex nA IIC T4 Gc
further information / internet links	
internet link	
<ul style="list-style-type: none"> to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool

- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

- <http://www.siemens.com/simatic-net>
- <https://mall.industry.siemens.com>
- <http://www.siemens.com/industry/infocenter>
- <http://automation.siemens.com/bilddb>
- <http://www.siemens.com/cax>
- <https://support.industry.siemens.com>

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

11/9/2023 