

**product type designation**

product description

**Cable RS422, Sub-D / M12**

Highly flexible communication line (6-core)

SIMATIC RF, MV plug-in cable, pre-assembled, between RF120C and reader PUR, trailing, length 5 m.



suitability for use

Plug-in cable for connecting a reader to the RF120C communication module

cable designation

L-YC11Y 6x1x0.25 6x24AWG CM

wire length

5 m

**electrical data**

number of electrical connections

2

type of electrical connection

Sub-D (male, 9 pin, 45°) / M12 (female, 8 pin, straight)

loop resistance per length / maximum

160 mΩ/m

insulation resistance coefficient

20 GΩ·m

operating voltage

- maximum

300 V

**mechanical data**

number of electrical cores

6

design of the shield

Braided shield made of tin-plated copper wires

outer diameter

- of cable sheath

5.4 mm

symmetrical tolerance of the outer diameter / of cable sheath

0.2 mm

material

- of the wire insulation
- of cable sheath

PVC

PUR

color

- of the insulation of data wires
- of cable sheath

DIN 47100

Black

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible
- with continuous bending

21.6 mm

43 mm

75 mm

number of bending cycles

3000000

tensile load / maximum

200 N

weight per length

45 kg/km

**ambient conditions**

ambient temperature

- during operation
- during storage
- during transport
- during installation

-30 ... +80 °C

-30 ... +80 °C

-30 ... +80 °C

-30 ... +80 °C

fire behavior

flame resistant according to IEC 60332-1-2

class of burning behaviour / according to EN 13501-6

Eca

chemical resistance

<ul style="list-style-type: none"> <li>• to mineral oil</li> </ul>	resistant
<ul style="list-style-type: none"> <li>• to grease</li> </ul>	resistant
radiological resistance / to UV radiation	resistant
<b>product features, product functions, product components / general</b>	
product feature	
<ul style="list-style-type: none"> <li>• halogen-free</li> </ul>	No
<ul style="list-style-type: none"> <li>• silicon-free</li> </ul>	Yes
<b>standards, specifications, approvals</b>	
UL/ETL listing / 300 V Rating	Yes; CM (only cable without plug)
certificate of suitability	
<ul style="list-style-type: none"> <li>• EAC approval</li> </ul>	Yes
reference code	
<ul style="list-style-type: none"> <li>• according to IEC 81346-2</li> </ul>	WG
<ul style="list-style-type: none"> <li>• according to IEC 81346-2:2019</li> </ul>	WGB
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>• to web page: selection aid TIA Selection Tool</li> </ul>	<a href="https://support.industry.siemens.com/cs/ww/en/view/67384964">https://support.industry.siemens.com/cs/ww/en/view/67384964</a>
<ul style="list-style-type: none"> <li>• to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/ident/rfid">http://www.siemens.com/ident/rfid</a>
<ul style="list-style-type: none"> <li>• to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>• to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>• to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>• to website: CAX-Download-Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>• to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>

**last modified:**

8/29/2023 