

product type designation



Figure similar

Antenna ANT 3 incl. antenna cable

RF300/RF200 antenna ANT 3 for connection to RF250R and RF350R IP67, -25 to +70 °C, dimensions 50x28x10 mm incl. antenna connection cable PUR, UL 758, length 3 m trailing plug M8 straight/M8 angled consisting of: 1x 6GT23981CD300AX0 1x 6GT23910AH30.

suitability for operation	RF250R / RF350R
radio frequencies	
transmission frequency / rated value	13.56 MHz
electrical data	
type of electrical connection / of the antenna	M8, 4-pin
design of plug-in connection	male
mechanical data	
material	PA6 V0
color	black
tightening torque / of the screw for securing the equipment / maximum	1 N·m
mounting distance	
• relating to metal surfaces / recommended / minimum	0 m
ambient conditions	
ambient temperature	
• during operation	-25 ... +70 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
protection class IP	IP67
shock resistance	according to EN 60721-3-7 Class 7M2
shock acceleration	500 m/s ²
vibrational acceleration	200 m/s ²
design, dimensions and weights	
width	28 mm
height	50 mm
depth	10 mm
net weight	160 g
fastening method	2 x M4 screws
wire length / of antenna cable	3 m
standards, specifications, approvals	
certificate of suitability	CE, FCC, IC, cULus
certificate of suitability	
• IECEx	Yes
• for IECEx / as marking	the ATEX approval of the connected reader applies
reference code / according to IEC 81346-2:2019	TFB
accessories	
accessories	Included: 6GT2391-0AH30 (antenna cable)
further information / internet links	

internet link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://support.industry.siemens.com/cs/ww/en/view/67384964>
<http://www.siemens.com/ident/rfid>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

8/29/2023 