## **SIEMENS**

Data sheet 6GT2800-4BB00

## product type designation



## RF340T transponder

SIMATIC RF300 Transponder RF340T 8 KB FRAM, IP67/X9K, -25 to +85  $^{\circ}\text{C}$  , 48x2 5x 15 mm, minimum order quantity 5 units.

suitability for operation	RF300
radio frequencies	
operating frequency / rated value	13.56 MHz
range / maximum	105 mm; range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	RF300-specific
transfer rate / with radio transmission / maximum	106 kbit/s
product feature / multitag-capable	Yes
electrical data	
product component / backup battery	No
memory	
type of memory	FRAM / EEPROM
storage capacity / of the user memory	8189 byte
type of memory organization	UID (fixed code) 4 bytes, user memory 8189 bytes, OTP memory 20 bytes
number of read cycles / at ambient temperature < 40 $^{\circ}\text{C}$ / maximum	1E+10
number of write cycles / at ambient temperature < 40 $^{\circ}\text{C}$ / maximum	1E+10
data retention time / at ambient temperature < 40 $^{\circ}\text{C}$ / not less than	10 a
property of memory	Block-by-block write protection of the OTP memory
mechanical data	
material	PA12
color	anthracite
mounting distance / relating to metal surfaces / recommended / minimum	0 mm
ambient conditions	
ambient temperature	
<ul> <li>during read/write access</li> </ul>	-25 +85 °C
outside the read/write area	-40 +85 °C
during storage	-40 +85 °C
protection class IP	IP67/IPx9K
shock resistance	According to DIN EN 60721-3-7 Class 7 M3
shock acceleration	500 m/s²
vibrational acceleration	200 m/s²
design, dimensions and weights	
width	25 mm
height	15 mm
depth	48 mm
net weight	25 g

fastening method	2 x M3 screws
product features, product functions, product components / general	
product feature	
• silicon-free	Yes
<ul><li>printable</li></ul>	No
standards, specifications, approvals	
certificate of suitability	
• IECEx	No
cULus approval	Yes
MTBF	1200 a
further information / internet links	
internet link	
<ul> <li>to web page: selection aid TIA Selection Tool</li> </ul>	https://support.industry.siemens.com/cs/ww/en/view/67384964
<ul> <li>to website: Industrial communication</li> </ul>	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/industry/infocenter
<ul><li>to website: Image database</li></ul>	http://automation.siemens.com/bilddb
<ul><li>to website: CAx-Download-Manager</li></ul>	http://www.siemens.com/cax
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com

last modified: 8/29/2023 🖸