

product type designation

Transponder RF630L (special variant)

SIMATIC RF630L (special variant) SmartLabel PET; 75x 20 mm; strongly adhesive on plastic ISO 18000-6C, EPC Class 1 Gen 2 Frequency 860 to 960 MHz, chip type NXP Ucode7XM+ EPC 448 Bit, user 2048-bit; Core diameter 76 mm 3500 units on one roll Minimum order quantity 7000 units .



Figure similar

suitability for operation

RF600

radio frequencies

operating frequency	860 ... 930 MHz
range / maximum	5 m; observe system manual RF600: overrange is possible, range is reader dependent: observe http://support.automation.siemens.com/WW/view/en/67384964
protocol / with radio transmission	EPCglobal Class 1 Gen 2 / ISO 18000-63
transfer rate / with radio transmission / maximum	320 kbit/s
product feature / multitag-capable	Yes
polarization	Linear

electrical data

product component / backup battery	No
------------------------------------	----

memory

type of memory	EEPROM
storage capacity / of the user memory	256 byte
type of memory organization	EPC memory 96 bit (12 byte) expandable up to 448 bit (56 byte), user memory 2048 bit (256 byte), TID memory 96 bit (12 byte)
number of read cycles / at ambient temperature < 40 °C / maximum	1E+14
number of write cycles / at ambient temperature < 40 °C / maximum	100000
data retention time / at ambient temperature < 40 °C / not less than	20 a
property of memory	lock, unlock, kill, write protection, password protection
type of transponder chip used	NXP UCODE 7xm-2K

mechanical data

material	PET
color	white
mounting distance / relating to metal surfaces / recommended / minimum	3 mm

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during read/write access outside the read/write area during storage 	<p>-25 ... +85 °C</p> <p>-40 ... +120 °C</p> <p>5 ... 25 °C</p>
ambient condition / for operation	Maximum storage life 2 years at 45% to 55% humidity, operating temperature permanent up to 85 °C, transient -40 °C to 120 °C for 90 minutes
protection class IP	IP67, when adhered
resistance to mechanical stress	Torsion and bending stress conditionally permissible

design, dimensions and weights

width	20 mm
height	0.3 mm
depth	75 mm
net weight	0.2 g
fastening method	one-side adhesive
product features, product functions, product components / general	
product feature	
• printable	Yes
printing process	Thermal transfer process
standards, specifications, approvals	
certificate of suitability	
• IECEx	No
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
last modified:	2/10/2022 