

product type designation

RF220R reader

SIMATIC RF200 reader RF220R; RS422 interface (3964R); IP67, -25 to +70 °C; M30x 71mm; with integrated antenna.



suitability for operation

ISO 15693 Transponder (MDS Dxxx), for connecting to communication modules

radio frequencies

operating frequency / rated value

13.56 MHz

range / maximum

35 mm; Range is dependent on transponder type: observe <http://support.automation.siemens.com/WW/view/en/67384964>

protocol / with radio transmission

ISO 15693, ISO 18000-3

transfer rate / with radio transmission / maximum

26.5 kbit/s

product feature / multitag-capable

No

electrical data

transfer rate / at the point-to-point connection / serial / maximum

115.2 kbit/s

transmission time / for user data

- for write access / per byte / typical
- for read access / per byte / typical

0.6 ms
0.6 ms

interfaces

standard for interfaces / for communication

RS422

type of electrical connection

M12, 8-pin

mechanical data

material

Brass, nickel-plated / PBT

color

silver/pastel turquoise

tightening torque / of the screw for securing the equipment / maximum

40 N·m

mounting distance / relating to metal surfaces / recommended / minimum

0 mm

supply voltage, current consumption, power loss

supply voltage

- at DC / rated value
- at DC

24 V
20.4 ... 28.8 V

consumed current / at DC

- at 24 V / typical

0.05 A

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-20 ... +70 °C
-25 ... +80 °C
-25 ... +80 °C

protection class IP

IP67

shock resistance

EN 60721-3-7 Class 7 M2

shock acceleration

500 m/s²

vibrational acceleration

200 m/s²

design, dimensions and weights

height	83 mm
diameter	30 mm
net weight	0.14 kg
fastening method	2 nuts M30 x 1.5 (included in scope of supply)
wire length	
• for RS 422 interface / maximum	1000 m
product features, product functions, product components / general	
display version	3-color LED
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
certificate of suitability	
• IECEX	No
MTBF	501 a
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

8/29/2023 