

### product type designation



### TIM 3V-IE Advanced

SINAUT ST7, TIM 3V-IE advanced communications module for SIMATIC S7-300 with an RS232 interface for SINAUT communication via a classic WAN and an RJ45 interface for SINAUT communication via an IP-based network (WAN or LAN).

transfer rate	
transfer rate	
<ul style="list-style-type: none"> <li>for Industrial Ethernet</li> </ul>	10 ... 100 Mbit/s
<ul style="list-style-type: none"> <li>according to RS 232</li> </ul>	50 ... 38400 bit/s
interfaces	
number of interfaces / according to Industrial Ethernet	1
number of electrical connections	
<ul style="list-style-type: none"> <li>for external data transmission / according to RS 232</li> </ul>	1
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>of Industrial Ethernet interface</li> </ul>	RJ45 port
type of electrical connection	
<ul style="list-style-type: none"> <li>at interface 1 / for external data transmission</li> </ul>	9 pin Sub-D-connector (RS232)
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	2-pole plugable terminal block
design of the removable storage	
<ul style="list-style-type: none"> <li>C-PLUG</li> </ul>	No
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	20.4 ... 28.8 V
supply voltage / external / at DC / rated value	24 V
supply voltage / external / at DC / rated value	20.4 ... 28.8 V
relative symmetrical tolerance / at DC	
<ul style="list-style-type: none"> <li>at 5 V</li> </ul>	5 %
relative positive tolerance / at DC / at 24 V	5 %
relative negative tolerance / at DC / at 24 V	5 %
consumed current	
<ul style="list-style-type: none"> <li>from backplane bus / at DC / at 24 V / maximum</li> </ul>	0.2 A
<ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / maximum</li> </ul>	0.2 A
power loss [W]	5.8 W
product extension / optional / backup battery	No
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> </ul>	0 ... 60 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %

protection class IP	IP20
<b>design, dimensions and weights</b>	
module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.25 kg
<b>product features, product functions, product components / general</b>	
number of units	Number of TIMs per S7-300: multiple, number depends on the connection resources of the S7-300 CPU
<ul style="list-style-type: none"> <li>note</li> </ul>	
wire length	6 m
<ul style="list-style-type: none"> <li>with RS 232 interface / maximum</li> </ul>	
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication	24
<ul style="list-style-type: none"> <li>maximum</li> </ul>	
<ul style="list-style-type: none"> <li>with PG connections / maximum</li> <li>with OP connections / maximum</li> </ul>	
service	Yes
<ul style="list-style-type: none"> <li>SINAUT ST7 via S7 communication</li> <li>PG/OP communication</li> </ul>	
<b>performance data / multi-protocol mode</b>	
number of active connections / with multi-protocol mode	24
<b>performance data / telecontrol</b>	
suitability for use	Yes
<ul style="list-style-type: none"> <li>node station</li> <li>substation</li> <li>TIM control center</li> <li>note</li> </ul>	
<ul style="list-style-type: none"> <li>note</li> </ul>	
<ul style="list-style-type: none"> <li>note</li> </ul>	
protocol / is supported	No
<ul style="list-style-type: none"> <li>DNP3</li> <li>SINAUT ST1 protocol</li> <li>SINAUT ST7 protocol</li> </ul>	
<ul style="list-style-type: none"> <li>SINAUT ST7 protocol</li> </ul>	
product function / data buffering if connection is aborted	Yes; 32,000 data messages
storage capacity	20 Kibyte
<ul style="list-style-type: none"> <li>of S7 CPU work memory / for TD7onCPU mode data blocks on CPU / required</li> <li>of S7 CPU work memory / for TD7onTIM mode data blocks on TIM / required</li> <li>note</li> </ul>	
<ul style="list-style-type: none"> <li>note</li> </ul>	
product feature / buffered message frame memory	No
transmission format	Yes
<ul style="list-style-type: none"> <li>for SINAUT ST1 protocol with polling / 11 bit</li> <li>for SINAUT ST1 protocol with spontaneous / 10-bit or 11-bit</li> <li>for SINAUT ST7 protocol with multi-master polling / 10-bit</li> <li>for SINAUT ST7 protocol with polling or spontaneous / 10-bit or 11-bit</li> </ul>	
<ul style="list-style-type: none"> <li>for SINAUT ST7 protocol with multi-master polling / 10-bit</li> </ul>	
<ul style="list-style-type: none"> <li>for SINAUT ST7 protocol with polling or spontaneous / 10-bit or 11-bit</li> </ul>	
operating mode for scanning of data transmission	Polling, polling with time slot procedure
<ul style="list-style-type: none"> <li>with dedicated line/radio link / with SINAUT ST1 protocol</li> <li>with dedicated line/radio link / with SINAUT ST7 protocol</li> </ul>	
<ul style="list-style-type: none"> <li>with dial-up network / with SINAUT ST1 protocol</li> <li>with dial-up network / with SINAUT ST7 protocol</li> </ul>	
<ul style="list-style-type: none"> <li>with dial-up network / with SINAUT ST1 protocol</li> <li>with dial-up network / with SINAUT ST7 protocol</li> </ul>	
hamming distance	4
<ul style="list-style-type: none"> <li>for SINAUT ST1 protocol</li> <li>for SINAUT ST7 protocol</li> </ul>	
<b>product functions / management, configuration, engineering</b>	
configuration software	SINAUT ST7 ES
<ul style="list-style-type: none"> <li>required</li> <li>for CPU configuring / required / SINAUT TD7 block library for CPU</li> </ul>	
<ul style="list-style-type: none"> <li>for CPU configuring / required / SINAUT TD7 block library for CPU</li> </ul>	

<ul style="list-style-type: none"> <li>for PG configuring / required / SINAUT ST7 configuration software for PG</li> </ul>	Yes
storage location / of TIM configuration data	on the TIM
<b>product functions / security</b>	
operating mode / Virtual Private Network (VPN)	Yes
type of authentication / with Virtual Private Network / PSK	Yes
product function	
<ul style="list-style-type: none"> <li>password protection for VPN</li> </ul>	Yes
<ul style="list-style-type: none"> <li>MSC client via GPRS modem with MSC capability</li> </ul>	Yes
protocol	
<ul style="list-style-type: none"> <li>is supported / MSC protocol</li> </ul>	Yes
<ul style="list-style-type: none"> <li>with Virtual Private Network MSC / is supported</li> </ul>	TCP/IP
key length / for MSC / with Virtual Private Network	128 bit
number of possible connections	
<ul style="list-style-type: none"> <li>as MSC client / with VPN connection</li> </ul>	1
<ul style="list-style-type: none"> <li>as MSC server / with VPN connection</li> </ul>	0
<b>standards, specifications, approvals / hazardous environments</b>	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
<ul style="list-style-type: none"> <li>as marking</li> </ul>	Ex nA IIC T4 Gc
<b>further information / internet links</b>	
internet link	
<ul style="list-style-type: none"> <li>to web page: selection aid TIA Selection Tool</li> </ul>	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
<ul style="list-style-type: none"> <li>to website: Industrial communication</li> </ul>	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
<ul style="list-style-type: none"> <li>to website: Industry Mall</li> </ul>	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
<ul style="list-style-type: none"> <li>to website: Information and Download Center</li> </ul>	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
<ul style="list-style-type: none"> <li>to website: Image database</li> </ul>	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
<ul style="list-style-type: none"> <li>to website: CAx-Download-Manager</li> </ul>	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
<ul style="list-style-type: none"> <li>to website: Industry Online Support</li> </ul>	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <a href="http://support.automation.siemens.com">http://support.automation.siemens.com</a> . (V3.4)

last modified:

8/30/2023 