

product type designation



TIM 4R-IE DNP3

TIM 4R-IE DNP3 communications module for SIMATIC S7-300, S7-400, PC; with two RS232/RS485 Interfaces for DNP3- Communication via standard WAN networks and two RJ45 interfaces for DNP3 communication via IP-based networks (WAN or LAN).

transfer rate	
transfer rate	
<ul style="list-style-type: none"> for Industrial Ethernet 	10 ... 100 Mbit/s
<ul style="list-style-type: none"> according to RS 232 	9600 ... 115200 bit/s
interfaces	
number of interfaces / according to Industrial Ethernet	2
number of electrical connections	
<ul style="list-style-type: none"> for external data transmission / according to RS 232 	2
<ul style="list-style-type: none"> for power supply 	1
type of electrical connection	
<ul style="list-style-type: none"> of Industrial Ethernet interface 	RJ45 port
type of electrical connection	
<ul style="list-style-type: none"> at interface 1 / for external data transmission 	9 pin Sub-D-connector, RS232 switchable to RS485
<ul style="list-style-type: none"> at interface 2 / for external data transmission 	9-pole D-sub connector, RS232 can be switched to RS485
<ul style="list-style-type: none"> for power supply 	2-pole plugable terminal block
design of the removable storage	
<ul style="list-style-type: none"> C-PLUG 	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	24 V
supply voltage	20.4 ... 28.8 V
supply voltage / external / at DC / rated value	24 V
supply voltage / external / at DC / rated value	20.4 ... 28.8 V
consumed current	
<ul style="list-style-type: none"> from backplane bus / at DC / at 24 V / maximum 	0.2 A
<ul style="list-style-type: none"> from external supply voltage / at DC / at 24 V / maximum 	0.17 A
power loss [W]	4.6 W
product extension / optional / backup battery	Yes
type of battery	Lithium AA / 3.6 V / 2.3 Ah
backup current	
<ul style="list-style-type: none"> typical 	100 μ A
<ul style="list-style-type: none"> maximum 	160 μ A
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-40 ... +70 °C
<ul style="list-style-type: none"> during transport 	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / 	95 %

maximum	
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-300 double width
width	80 mm
height	125 mm
depth	120 mm
net weight	0.4 kg
product features, product functions, product components / general	
number of units	
• note	Number of TIMs per S7-300 / S7-400: 1
wire length	
• with RS 232 interface / maximum	6 m
• with RS 485 interface / maximum	30 m
performance data / S7 communication	
number of possible connections / for S7 communication	
• maximum	5; only via LAN
• with PG connections / maximum	2
• with OP connections / maximum	1
service	
• PG/OP communication	Yes
performance data / telecontrol	
suitability for use	
• node station	Yes
• substation	Yes
• TIM control center	Yes
protocol / is supported	
• DNP3	Yes
• SINAUT ST1 protocol	No
• SINAUT ST7 protocol	No
• Modbus RTU	Yes
product function / data buffering if connection is aborted	Yes; 200,000 data points with one master
number of DNP3 masters	
• for Ethernet / maximum	8
• with RS 232 interface / maximum	1
number of Modbus RTU slaves / maximum	1
product functions / management, configuration, engineering	
configuration software	
• required	SINAUT ST7 ES
storage location / of TIM configuration data	on the CPU or TIM
product functions / time	
product component / hardware real time clock	Yes
product feature / hardware real time clock w. battery backup	Yes
accuracy / of the hardware real time clock / per day / maximum	4 s
time synchronization	
• from NTP-server	Yes
standards, specifications, approvals / hazardous environments	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
• as marking	Ex nA IIC T4 Gc
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com
security information	

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

8/30/2023 