

**Accessories**  
**CB 450/7.5 BLACK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



CB cable ties for the fastening of cables and markers.

- They are particularly suitable for fastening CLI M, SFX, WKM and WKS cable markers
- IEC 62275: 2006-conformant
- Fracture-resistant polyamide PA 6.6 with flammability rating V2 to UL-94

**General ordering data**

Type	CB 450/7.5 BLACK
Order No.	<a href="#">7940006071</a>
Version	Cable ties, Height x width: 450 x 7.8 mm, Polyamide 66, 540 N
GTIN (EAN)	4032248520268
Qty.	100 pc(s).

**Data sheet**

**Accessories  
CB 450/7.5 BLACK**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Width	7.8 mm	Width (inches)	0.307 inch
Height	450 mm	Height (inches)	17.716 inch
Depth	1.75 mm	Depth (inches)	0.069 inch
Net weight	5.87 g		

**Installation materials**

Cable diameter, max.	130 mm	Material	Polyamide 66
Operating temperature range, max.	85 °C	Operating temperature range, min.	-40 °C
Tensile strength	540 N	UL 94 flammability rating	V-2

**Classifications**

ETIM 6.0	EC000046	ETIM 7.0	EC000046
eClass 9.0	27-14-07-02	eClass 9.1	27-14-07-02
eClass 10.0	27-14-07-02	UNSPSC	30-21-18-01

**Approvals**

Approvals



ROHS Conform

**Downloads**

Approval/Certificate/Document of Conformity	<a href="#">DE PI830000160627_002</a>
Engineering Data	<a href="#">EPLAN_WSCAD</a>

**Data sheet**

**Accessories**  
**CB 450/7.5 BLACK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

