



Cabinet cooling unit KG 8512-230V



Product Features


Brand Name:	SlimLine Pro	
Order Number:	851200001	
Color:	RAL 7035	
Housing Material:	Mild steel, powder coated	
Ingress protection:	IP 56 / Type 12,3,3R, 4	
Note:	pat. D815,265	
Approvals:	CE, RoHS	
Accessories:	Aluminum filter	
	Cold air outlet duct	
Taric Code:	84158200	

Technical data KG 8512-230V

Cooling capacity L35L35:	1.2 kW @ 50 Hz 1.2 kW @ 60 Hz
Cooling capacity L35L50:	900 W @ 50 Hz 900 W @ 60 Hz
Compressor:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	220 g / 7.76 oz.
High / low pressure:	6 / 30 bar 87 / 435 psig
Temperature range:	10°C - +60°C
Air volume flow (system / unimpeded):	Ambient air circuit: 300 / 550 m ³ /h Cabinet air circuit: 350 / 550 m ³ /h
Mounting:	External / recessed
Dimension H x W x D:	950 x 305 x 210 mm
Weight:	30 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	3.2 A
Starting current:	15 A
Max. current:	4.4 A
Nominal power L35L35:	715 W
Max. power:	1 kW
Fuse:	8 A (T)
Connection:	5 pole terminal for signals 4 pole terminal for power


Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview product group Cabinet cooling units - SlimLine Pro](#)

Performance Graph:




[click image to enlarge](#)

Cut out dimensions:



[click image to enlarge](#)

Product Accessories:



[click image to enlarge](#)