



Cabinet cooling unit KG 8515-230V



Product Features

Brand Name:	SlimLine Pro
Order Number:	851500001
Color:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress protection:	IP 56 / Type 12,3,3R, 4
Note:	pat. D815,265
Approvals:	CE, RoHS

Accessories:	Aluminum filter	
	Cold air outlet duct	
Taric Code:	84158200	

Technical data KG 8515-230V

Cooling capacity L35L35:	1.5 kW @ 50 Hz 1.5 kW @ 60 Hz
Cooling capacity L35L50:	1.3 kW @ 50 Hz 1.3 kW @ 60 Hz
Compressor:	Rotary piston
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	320 g / 11.29 oz.
High / low pressure:	6 / 30 bar 87 / 435 psig
Temperature range:	10°C - +60°C
Air volume flow (system / unimpeded):	Ambient air circuit: 550 / 850 m ³ /h Cabinet air circuit: 500 / 850 m ³ /h
Mounting:	External / recessed
Dimension H x W x D:	1,350 x 395 x 210 mm
Weight:	41 kg
Voltage / Frequency:	230 V ~ 50/60 Hz
Current L35L35:	2.9 A
Starting current:	16 A
Max. current:	4.7 A
Nominal power L35L35:	650 W
Max. power:	1.1 kW
Fuse:	8 A (T)
Connection:	5 pole terminal for signals 4 pole terminal for power

Please click on the graphics to download.
 More CAD drawings can be found under [Product Download](#).
 > [Overview product group Cabinet cooling units - SlimLine Pro](#)

