



Buzzer element, continuous tone or pulsating, adjustable, 85 dB, black, 115 V AC, diameter 70 mm

product brand name	SIRIUS	
product designation	Buzzer element	
<b>General technical data</b>		
product function adjustable acoustic signal	Yes	
type of voltage of the operating voltage	AC	
operating voltage		
• 1 at AC at 50 Hz rated value	115 V	
• 1 at AC at 60 Hz rated value	115 V	
relative positive tolerance of the operating voltage	10 %	
relative negative tolerance of the operating voltage	-10 %	
consumed current maximum	25 mA	
tone frequency		
• 1	1.75 kHz	
reference code according to EN 61346-2	P	
<b>Acoustic signal</b>		
type of acoustic signal	continuous tone / pulse tone	
service life of acoustic signal device	5 000 h	
loudness level	85 dB	
loudness level	85 ... 85 dB	
tone frequency of alternating tone	1.75 ... 1.75 kHz	
<b>Enclosure</b>		
height	72 mm	
width	70 mm	
outer diameter of the signal column element	70 mm	
material	PC	
color	black	
fastening method	Bayonet	
protection class IP	IP65	
<b>Ambient conditions</b>		
ambient temperature during operation	-20 ... +50 °C	
<b>Certificates/ approvals</b>		
General Product Approval	EMC	Declaration of Conformity

[Confirmation](#)



other

**Further information**

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4440-0FA>

**Cax online generator**



<http://support.automation.siemens.com/WWW/CAXorder/default.aspx?lang=en&mlfb=8WD4440-0FA>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**


<https://support.industry.siemens.com/cs/ww/en/ps/8WD4440-0FA>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=8WD4440-0FA&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4440-0FA&lang=en)



**-P**



last modified:

8/29/2023 