

PZ 6/5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Crimping tools for wire end ferrules, with and without plastic collars**

- Ratchet guarantees precise crimping
- Release option in the event of incorrect operation

General ordering data

| | |
|-------------------|--|
| Version | Pressing tool, Crimping tool for wire-end ferrules, 0.25mm ² , 6mm ² , Trapezoidal indentation crimp |
| Order No. | 9011460000 |
| Type | PZ 6/5 |
| GTIN (EAN) | 4008 190165352 |
| Qty. | 1 pc(s). |
| Replacement parts | 9011620000 9202810000 |

Creation date May 31, 2022 3:10:51 PM CEST

Catalogue status 20.05.2022 / We reserve the right to make technical changes.

PZ 6/5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|--------|----------------|------------|
| Width | 200 mm | Width (inches) | 7.874 inch |
| Net weight | 433 g | | |

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

Technical data

| | | | |
|------------------------|--|---------|---|
| Description of article | Crimping tool for wire end ferrules with/without plastic collar, 0.25 to 6 mm ² | Version | Mechanical, without interchangeable inserts |
|------------------------|--|---------|---|

Description of contact

| | | | |
|-----------------------------------|--|-----------------------------------|----------------------|
| Conductor cross-section, max. AWG | AWG 10 | Conductor cross-section, min. AWG | AWG 24 |
| Crimping range, max. | 6 mm ² | Crimping range, min. | 0.25 mm ² |
| Type of contact | Wire-end ferrules with/without plastic collars | | |

tool data crimping

| | | | |
|---------------------------------------|---------------------|---------------------------------------|-------------------------------|
| Crimping profile 1, max. | 0.5 mm ² | Crimping profile 1, min. | 0.25 mm ² |
| Crimping profile 2, max. | 1.5 mm ² | Crimping profile 2, min. | 0.75 mm ² |
| Crimping profile 3, min. | 2.5 mm ² | Crimping profile 4, min. | 4 mm ² |
| Crimping profile 5 | 6 mm ² | Crimping type/profile | Trapezoidal indentation crimp |
| Wire end ferrules cross-section, max. | 6 mm ² | Wire end ferrules cross-section, min. | 0.25 mm ² |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000168 | ETIM 7.0 | EC000168 |
| ETIM 8.0 | EC000168 | ECLASS 9.0 | 21-04-38-11 |
| ECLASS 9.1 | 21-04-38-11 | ECLASS 10.0 | 21-04-38-11 |
| ECLASS 11.0 | 21-04-38-11 | ECLASS 12.0 | 21-04-38-11 |

Approvals

Approvals



Downloads

| | |
|--------------------|--|
| Engineering Data | WSCAD |
| User Documentation | Manual |
| Catalogues | Catalogues in PDF-format |
| Brochures | |

Creation date May 31, 2022 3:10:51 PM CEST

Catalogue status 20.05.2022 / We reserve the right to make technical changes.

Data sheet

PZ 6/5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

