

**LIR 1,5M8 V****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

**General ordering data**

Version	cable lug, terminal end, Insulated cable connector, 1.5 mm <sup>2</sup> , 0.5 mm <sup>2</sup> - 1.5 mm <sup>2</sup>
Order No.	<a href="#">9200120000</a>
Type	LIR 1,5M8 V
GTIN (EAN)	4032248409747
Qty.	100 pc(s).

Creation date May 31, 2022 4:55:21 PM CEST

Catalogue status 20.05.2022 / We reserve the right to make technical changes.

## LIR 1,5M8 V

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Depth	5.9 mm	Depth (inches)	0.232 inch
Width	28.1 mm	Width (inches)	1.106 inch
Net weight	0.7 g		

## Technical data

Description of article	Insulated ring-cable connector 1.5 mm <sup>2</sup> / M8
------------------------	---

## Connectors

Conductor cross-section	1.5 mm <sup>2</sup>	Conductor cross-section, max.	1.5 mm <sup>2</sup>
Conductor cross-section, min.	0.5 mm <sup>2</sup>	Connection density (S1)	0.75 mm
Dimension	M 8	Dimension (bolt)	M 8
Identification colour	red	Inside diameter (d1)	8.4 mm
Insulation	Available	Material/plastic	PVC
Outside diameter (d)	11.6 mm	Plastic collar diameter (D)	4 mm
Plastic collar length (b)	11.3 mm		

## Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ETIM 8.0	EC001059	ECLASS 9.0	27-40-02-92
ECLASS 9.1	27-40-02-12	ECLASS 10.0	27-40-02-92
ECLASS 11.0	27-40-02-92	ECLASS 12.0	27-40-02-92

## Approvals

Approvals



ROHS Conform

## Downloads

Engineering Data	<a href="#">EPLAN</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	