

LIR 2,5M8 V

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Insulated ring-cable connector made from PVC

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 2.5 mm ² , 1.5 mm ² - 2.5 mm ²
Order No.	9200200000
Type	LIR 2,5M8 V
GTIN (EAN)	40322484 10026
Qty.	100 pc(s).

Creation date May 31, 2022 5:15:37 PM CEST

Catalogue status 20.05.2022 / We reserve the right to make technical changes.

LIR 2,5M8 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	6.2 mm	Depth (inches)	0.244 inch
Width	29.3 mm	Width (inches)	1.154 inch
Net weight	1.002 g		

Technical data

Description of article	Insulated ring-cable connector 2.5 mm ² / M8
------------------------	---

Connectors

Conductor cross-section	2.5 mm ²	Conductor cross-section, max.	2.5 mm ²
Conductor cross-section, min.	1.5 mm ²	Connection density (S1)	0.8 mm
Dimension	M 8	Dimension (bolt)	M 8
Identification colour	blue	Inside diameter (d1)	8.4 mm
Insulation	Available	Material/plastic	PVC
Outside diameter (d)	14 mm	Plastic collar diameter (D)	4.5 mm
Plastic collar length (b)	11.3 mm		

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ETIM 8.0	EC001059	ECLASS 9.0	27-40-02-92
ECLASS 9.1	27-40-02-12	ECLASS 10.0	27-40-02-92
ECLASS 11.0	27-40-02-92	ECLASS 12.0	27-40-02-92

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data	EPLAN
Catalogues	Catalogues in PDF-format
Brochures	