

**LIP 1,5R12 V**

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



**Insulated pin-cable connector made from PVC or PC/PA**

- Conventional designs
- Not soldered
- With conical entry funnel

**General ordering data**

|            |   |
|------------|---|
| Version    | cable lug, terminal end, Insulated cable connector, 0.5 mm <sup>2</sup> - 1.5 mm <sup>2</sup> , red |
| Order No.  | <a href="#">9200460000</a>  |
| Type       | LIP 1,5R12 V  |
| GTIN (EAN) | 4032248410309   |
| Qty.       | 100 pc(s).  |

**LIP 1,5R12 V**

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

**Technical data**

**Dimensions and weights**

|            |         |                |            |
|------------|---------|----------------|------------|
| Depth      | 5.8 mm  | Depth (inches) | 0.228 inch |
| Width      | 23.3 mm | Width (inches) | 0.917 inch |
| Net weight | 0.71 g  |                |            |

**Technical data**

|                        |   |
|------------------------|---|
| Description of article | Insulated pin-cable connector 1.5 mm <sup>2</sup> L=12 mm |
|------------------------|---|

**Connectors**

|                                |                     |                               |                     |
|--------------------------------|---------------------|-------------------------------|---------------------|
| Conductor cross-section, max.  | 1.5 mm <sup>2</sup> | Conductor cross-section, min. | 0.5 mm <sup>2</sup> |
| Dimension                      | 12.0 mm             | Dimension (pin length)        | 12 mm               |
| Identification colour          | red                 | Insulation                    | Available           |
| Length 1 (l1)                  | 22 mm               | Material/plastic              | PVC                 |
| Outside diameter of shaft (d3) | 1.9 mm              | Plastic collar diameter (D)   | 4.3 mm              |
| Plastic collar length (b)      | 10 mm               |                               |                     |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001059    | ETIM 7.0    | EC001059    |
| ETIM 8.0    | EC001059    | ECLASS 9.0  | 27-40-02-92 |
| ECLASS 9.1  | 27-40-02-12 | ECLASS 10.0 | 27-40-02-92 |
| ECLASS 11.0 | 27-40-02-92 | ECLASS 12.0 | 27-40-02-92 |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">EPLAN</a>                    |
| Catalogues       | <a href="#">Catalogues in PDF-format</a> |
| Brochures        |  |

**Data sheet**

**LIP 1,5R12 V**

**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

[info@weidmueller.com](mailto:info@weidmueller.com)

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

