

KT 55**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



Cutting tools in mechanical ratchet version. Suitable for non-pinch cutting of copper and aluminium conductors. Easy operation thanks to optimum leverage and a cleverly engineered cam mechanism.

General ordering data

Version	Cutting tools, Circular cable cutter
Order No.	9202060000
Type	KT 55
GTIN (EAN)	4032248482191
Qty.	1 pc(s).

KT 55

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmuller.com

www.weidmuller.com

Technical data

Dimensions and weights

Depth	45 mm	Depth (inches)	1.772 inch
Height	115 mm	Height (inches)	4.528 inch
Width	365 mm	Width (inches)	14.37 inch
Net weight	1,486.7 g		

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data

Description of article	Front cable cutter up to 55 mm outer diameter	Version	One-hand mechanical
------------------------	---	---------	---------------------

Cutting tools

Aluminium sector cable	4 x 150 SE	Copper cable - flexible, max.	500 mm ²
Copper cable - flexible, max. (kcmil)	1,000 kcmil	Copper cable - stranded, max.	500 mm ²
Copper cable - stranded, max. (kcmil)	1,000 kcmil	Copper cable, max. diameter	55 mm
Copper sector cable	3 x 150 SM	Data / telephone / control cable, max. Ø	55 mm
Stranded aluminium cable, max (mm ²)	500 mm ²	Stranded aluminium cable, max. (kcmil)	1,000 kcmil
Stranded aluminium cable, max. diameter	55 mm		

Classifications

ETIM 6.0	EC000142	ETIM 7.0	EC000142
ETIM 8.0	EC000142	ECLASS 9.0	21-04-47-01
ECLASS 9.1	21-04-90-11	ECLASS 10.0	21-04-47-01
ECLASS 11.0	21-04-47-01	ECLASS 12.0	21-04-47-01

Approvals

Approvals



Downloads

User Documentation	Manual
Catalogues	Catalogues in PDF-format
Brochures	

KT 55

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold




Tel. +49 5231 14-0

Fax. +49 5231 14-2083

Drawings

Example of use

info@weidmueller.com

-  Cu + Al: max. 55 mm
-  Cu: max. 500 mm²
Al: max. 500 mm²
-  Cu: max. 500 mm²

