

KT 80**Weidmüller Interfaces GmbH & Co. KG**

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com



Cutting tools in mechanical ratchet version. Suitable for non-pinch cutting of copper and aluminium conductors. Easy operation thanks to optimum leverage and a cleverly engineered cam mechanism.

General ordering data

Version	Cutting tools, Circular cable cutter
Order No.	9202080000
Type	KT 80
GTIN (EAN)	4032248482313
Qty.	1 pc(s).

KT 80

Weidmüller Interfaces GmbH & Co. KG

Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com

www.weidmueller.com

Technical data

Dimensions and weights

Depth	55 mm	Depth (inches)	2.165 inch
Height	175 mm	Height (inches)	6.89 inch
Width	675 mm	Width (inches)	26.575 inch
Net weight	3,500 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Description of article	Front cable cutter up to 80 mm outer diameter	Version	One-hand mechanical
------------------------	---	---------	---------------------

Cutting tools

Aluminium sector cable	4 x 240 SE	Copper cable - flexible, max.	630 mm ²
Copper cable - flexible, max. (kcmil)	1,260 kcmil	Copper cable - stranded, max.	630 mm ²
Copper cable - stranded, max. (kcmil)	1,260 kcmil	Copper cable, max. diameter	80 mm
Copper sector cable	3 x 240 SM	Data / telephone / control cable, max. Ø	80 mm
Stranded aluminium cable, max (mm ²)	1,000 mm ²	Stranded aluminium cable, max. (kcmil)	2,000 kcmil

Classifications

ETIM 6.0	EC000142	ETIM 7.0	EC000142
ETIM 8.0	EC000142	ECLASS 9.0	21-04-47-01
ECLASS 9.1	21-04-90-11	ECLASS 10.0	21-04-47-01
ECLASS 11.0	21-04-47-01	ECLASS 12.0	21-04-47-01

Approvals

Approvals



Downloads

User Documentation	Manual
Catalogues	Catalogues in PDF-format
Brochures	

KT 80**Weidmüller Interfaces GmbH & Co. KG**




Postfach 3030

32760 Detmold

Tel. +49 5231 14-0

Fax. +49 5231 14-2083

info@weidmueller.com**Drawings****Example of use**

-  Cu + Al: max. 80 mm
-  Cu: max. 630 mm²
Al: max. 1000 mm²
-  Cu: max. 630 mm²

