

POK MOPL 1656

Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26 D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration







The Klippon[®] POK enclosure range is made from a high-quality glass fibre reinforced polyester and is ideal for applications and environments where corrosion resistance, impact resistance and a high IP protection class are a requirement.

Key features of the extensive product range:

- Available in 17 sizes
- Two standard finishes (colours): grey (similar to RAL 7001 for industrial use) and black (similar to RAL 9011 for harsh environments, Ex)
- Cover with stainless steel screws in cross-head / slotted design
- Moulded gasket made of silicone or chloroprene
- Fixing holes outside the sealed area to ensure high ingress protection of IP66
- Impact resistance up to 7 Joules
- Mounting directly in the enclosure or using an internal mounting plate
- Direct wall mounting possible using fixing holes or mounting feet
- Fastening thread to attach mounting rails and plates
- Up to E60 fire rating dependent on the configuration
- Weidmüller can manufacture and supply this enclosure to match customer specifications - fitted with all necessary terminals and cable glands.

General ordering data

| Klippon POK (polyester empty enclosure), |
|---|
| Mounting plate, Height: 143 mm, Width: 545 mm, |
| Depth: 1.5 mm, Material: Sheet steel, galvanized, |
| Miscellaneous, silver |
| <u>9510710000</u> |
| POK MOPL 1656 |
| 4008190498276 |
| 1 pc(s). |
| |



POK MOPL 1656

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

Technical data

Dimensions and weights

| Depth | 1.5 mm | Depth (inches) | 0.059 inch |
|-----------------------------|--------|----------------------------|-------------|
| Height | 143 mm | Height (inches) | 5.63 inch |
| Width | 545 mm | Width (inches) | 21.457 inch |
| Mounting dimension - height | 76 mm | Mounting dimension - width | 532 mm |
| Net weight | 540 g | | |

Certificate numbers enclosure

| Certificate No. (| FΔC) | RUC-DE.BE02.B.00173 |
|-------------------|------|----------------------|
| Certificate No. (| LAC) | 1100-01.0102.0.00173 |

General information

| Material | Sheet steel, galvanized | Material thickness | 1.5 mm |
|----------------|-------------------------|--------------------|-----------------|
| Surface finish | Miscellaneous | Type of fixing | when screwed in |

Classifications

| ETIM 6.0 | EC000213 | ETIM 7.0 | EC000213 |
|-------------|-------------|-------------|-------------|
| ETIM 8.0 | EC000213 | ECLASS 9.0 | 27-40-06-39 |
| ECLASS 9.1 | 27-18-92-90 | ECLASS 10.0 | 27-40-06-39 |
| ECLASS 11.0 | 27-40-06-39 | ECLASS 12.0 | 27-40-06-39 |

Approvals

Approvals



ROHS Conform

Downloads

| Engineering Data | CAD data – STEP | |
|------------------|--------------------------|--|
| Engineering Data | EPLAN, WSCAD | |
| Catalogues | Catalogues in PDF-format | |
| Brochures | | |