



PRODUCTS

Search input field with magnifying glass icon

PRODUCTS

A-5292D

A-5292D

分享到 (http://www.facebook.com/sharer/sharer.php?

u=https%3a%2f%2fm1.hocom.tw%2fh%2fServiceDetail%3fkey%3dx9ic2%26set%3d7%26cont%3d25022) (https://social-plugins.line.me/lineit/share?url=https%3a%2f%2fm1.hocom.tw%2fh%2fServiceDetail%3fkey%3dx9ic2%26set%3d7%26cont%3d25022)

Download **Software(right click save to): USB Driver**
(http://www.yottacontrol.com/download/A5X_USB_DRIVER.rar), YottaE
(http://www.yottacontrol.com/download/YOTTA_UTY.rar)ditor
(http://www.yottacontrol.com/download/ye2.rar) **Documents(right click save to): Catalog**
(http://www.yottacontrol.com/download/52X_DM_E.pdf), **Manual**
(http://www.yottacontrol.com/new2019/download/Control_Manual_ENG.pdf)

Specifications

4AI(0/2~10V*2+PT_100/1000*2) ^{撥打電話} 2AO(0/2~10V) · 2DI · 2DO(Source Output) · Wi-Fi*1 · RS-485*1 · USB2.0*1

為提供您最佳個人化且即時服務，本網站透過使用 Cookies 記錄與存取您的瀏覽使用訊息。當您使用本網
前表示您同意 YottaControl 技術支援。 Learn more (/web/Home/CookiePrivacyPolicy) 接受並關閉



Operation Voltage: 10~30VDC / 24VAC
Inputs: 2*Isolation DI, status low:<1VDC, status high:>5~30VDC
Outputs: 2*(Transistor)
Continuous Current: 10-35VDC(1A)
Communication Baud Rate: 2400~921600bps
Isolation: YES(5000VDC)
Input Operating Frequency: 10HZ
Output Operating Frequency: Transistor 10HZ
Operation Temperature: -20 to +75 °C
Degree Of Protection: IP20
Installation: 35 mm DIN rail or Flush mounting
Dimension (W x H x D mm): 76.4*118.2*38.5 mm
Analog Inputs: 4
Analog Input Type: 2*0/2~10V, 2*PT-100/1000 (-200 ~ +600 °C)
Analog Outputs: 2*0/2~10V
Interface: WIFI + RS-485 + USB

Product List

A-52x series controller, support protocol: Modbus RTU/ASCII, Modbus over TCP/IP; Modbus over UDP/IP;

A-5288D	Wi-Fi Display CPU	LCM · DC Power Supply	8DI/4DO · RELAY Output ·	Wi-Fi*1 · RS-232*1 · RS-485*2 · USB2.0*1
A-5288D-T	Wi-Fi Display CPU	LCM · DC Power Supply	8DI/4DO · Transistors Output ·	Wi-Fi*1 · RS-232*1 · RS-485*2 · USB2.0*1
A-5289D	Wi-Fi Display CPU	LCM · DC Power Supply	4DI/4AI/4DO · RELAY Output ·	Wi-Fi*1 · RS-232*1 · RS-485*2 · USB2.0*1
A-5289D-T	Wi-Fi Display CPU	LCM · DC Power Supply	4DI/4AI/4DO · Transistors Output ·	Wi-Fi*1 · RS-232*1 · RS-485*2 · USB2.0*1
A-5290D	Wi-Fi Display CPU	LCM · DC Power Supply	4AI(0/4~20mA*2+PT-100/1000*2) ·	Wi-Fi*1 · RS-485*1 · USB2.0*1
A-5292D	Wi-Fi Display CPU	LCM · DC Power Supply	4AI(0/2~10V*2+PT-100/1000*2) ·	Wi-Fi*1 · RS-485*1 · USB2.0*1

Yottacontrol 巨控自動化股份有限公司

8F-1, No. 286-3, Hsin-Ya Rd, Chien-Chen Zone (80673) Kaohsiung, Taiwan
 為提供您最佳個人化且即時服務，本網站透過使用“Cookies”記錄與存取您的瀏覽使用訊息。當您使用本網
 站，即表示您同意 Cookies 技術支援。 Learn more (/web/Home/CookiePrivacyPolicy) 接受並關閉

886-7-812-6559

service@yottacontrol.com (mailto:service@yottacontrol.com)

08:00AM~17:00PM

SHARE

Y f S
 (http://m1.hocom.tw/serviceDetail?key=x9ic2&set=7&cont=25022)