



99000000

DDDT

The **Electro "D" range** of control and timing devices are compact modular units for easy introduction into standard panels and/or distribution boards. They mount directly onto DIN rail and align with standard miniature circuit breakers (MCB's).

• Compact DIN rail mounting: (H) 92 x (W) 36 x (D) 64 mm - (2 modules wide)

| type | supply | time | function | description |
|------|------------------|-------|-----------|-------------|
| турс | voltage ∗ | range | Tariotion | description |

Digital counter/times

Multi-function four digit counter/timer designed with the latest microprocessor technology. Setup and ranges can be adjusted with an easy to access and control menu system to make all common function available.

- · 4 digit count (up/down) with selectable prescaler
- Timer (up/down) with pulse start/stop
- 4 time ranges: 999.9s 9999 min

| DDCT230A | 230 VAC | 999.9 -9999 | timer | counter / timer |
|----------|---------|-------------|-------|-----------------|
|----------|---------|-------------|-------|-----------------|

Digital temperature controller with timer (interfaces with TP1 digital probe)

Multi-function/range digital temperature controller with four digit counter/timer designed with the latest microprocessor technology. Setup and ranges can be adjusted with an easy to access and control menu system to make all common function available.

- · Two set points / relay outputs / PID control
- · Over / under temperature

| DDTC230A | 230 VAC | _ | controller | digital temperature controller |
|-----------|---------|---|------------|------------------------------------|
| DDTCT230A | 230 VAC | _ | controller | temp controller with 24 hour clock |
| TP1 | _ | _ | _ | temperature probe |

Digital voltage window comparator timer

Multi-function/range digital voltage window comparator timer for monitoring supply voltage between two levels.

- Over and under voltage and frequency monitoring
- 2 relay outputs for individual function
- · Adjustable delays
- · Phase reversal on 3 phase units
- · Separate supply

| type | supply voltage* | phase | function | description |
|-----------|--------------------|-------|----------|-----------------------|
| DDVW3400A | 400 VAC | three | timer | digital voltage timer |

Digital current window comparator timer (can interface with 5A CT's)

Multi-function digital current window comparator for monitoring current between two levels.

- Over and under current and frequency monitoring
- 2 relay outputs for individual function
- Adjustable delays
- Separate supply

| DDCW3230A | 230 VAC | three | timer | digital current timer |
|-----------|---------|-------|-------|-----------------------|
| DDCW3400A | 400 VAC | three | timer | digital current timer |

* Other voltage options available on request.

Handheld radio (wireless) variable speed drive controller (DIN Rad

New radio wireless variable speed drive controller designed to interface with PLC function of variable speed drives.

• Handheld remote 800m transmission (line of sight)

| | | • | 3 , | |
|------|----------------|---------------|-------------|-------------------------|
| type | inputs | outputs | function | description |
| DRR | 12 or 24V ACDC | 5 solid state | receiver | radio VSD controller |
| DRT | _ | _ | transmitter | handheld VSD controller |
| ANT2 | _ | - | antenna | for DRR module |

Wireless signal extender (3 inputs and 3 outputs: Tx and Rx)

- Power supply: 12 or 24V ACDC
- License free radio band
- 7km transmission line of sight (includes Watchdog protection)

| DRC/M DRC/S | 3 3 | 3 relay 3 relay | master transceiver slave transceiver | wireless signal extender wireless signal extender |
|----------------|--------|--------------------|--------------------------------------|---|
| ANT2 | - | _ | antenna | per each DRC module |



