



2232...



2234...



02235



192100240000

Modular contactors 25A

- Modular DIN rail mount
- Auto - On - Off selector
- Continuous duty coils and contacts
- AC/DC silent coil (*with varistor protection*)
- Mechanical flag and LED indicators as standard
- Clip-on auxiliary contact module available (1NO+1NC or 2NO)
- Protective separation (*reinforced insulation*) between coil and contacts

type	rated power		description	modules width in 17.5 mm	contact configuration	coil voltage AC/DC
	AC-1 (A)	AC-3 kW (230V)				

2 pole modular contactor 25A (H) 89 x (W) 17.5 (D) 61 mm

- Compact (*one module wide*) 17.5 mm

223200124340	25A	1.0 kW *	modular contactor	1	2 NO	12V
223200244340	25A	1.0 kW *	modular contactor	1	2 NO	24V
223200484340	25A	1.0 kW *	modular contactor	1	2 NO	48V
223202304340	25A	1.0 kW *	modular contactor	1	2 NO	230V
223200124440	25A	1.0 kW *	modular contactor	1	2 NC	12V
223200244440	25A	1.0 kW *	modular contactor	1	2 NC	24V
223202304440	25A	1.0 kW *	modular contactor	1	2 NC	230V
223200124540	25A	1.0 kW *	modular contactor	1	1NO + 1NC	12V
223200244540	25A	1.0 kW *	modular contactor	1	1NO + 1NC	24V
223200484540	25A	1.0 kW *	modular contactor	1	1NO + 1NC	48V
223202304540	25A	1.0 kW *	modular contactor	1	1NO + 1NC	230V

* Single phase motor rating 230 VAC

4 pole modular contactor 25A (H) 89 x (W) 35 (D) 61 mm

type	rated power		description	modules width in 17.5 mm	contact configuration	coil voltage AC/DC
	AC-1 (A)	AC-3 kW (400V)				

- Compact (*two modules wide*) 35 mm

223400124340	25A	4.0 kW	modular contactor	2	4 NO	12V
223400244340	25A	4.0 kW	modular contactor	2	4 NO	24V
223402304340	25A	4.0 kW	modular contactor	2	4 NO	230V
223400124740	25A	4.0 kW	modular contactor	2	3NO + 1NC	12V
223400244740	25A	4.0 kW	modular contactor	2	3NO + 1NC	24V
223402304740	25A	4.0 kW	modular contactor	2	3NO + 1NC	230V
223400124640	25A	4.0 kW	modular contactor	2	2NO + 2NC	12V
223400244640	25A	4.0 kW	modular contactor	2	2NO + 2NC	24V
223402304640	25A	4.0 kW	modular contactor	2	2NO + 2NC	230V

Accessories for above contactors

Clip-on auxiliaries for above contactors (H) 84 x (W) 8.8 (D) 61 mm

02235	6A	clip-on auxiliary contact block	0.5	1NO + 1NC		
02233	6A	clip-on auxiliary contact block	0.5	2 NO		
02218	8-way	jumper link for 2 pole contactors	1	17.5 mm	blue	
02226	6-way	jumper link for 4 pole contactors	2	35 mm	blue	
02001	adaptor	chassis mounting adaptor	1	17.5 mm		
01101	adaptor	chassis mounting adaptor	2	35 mm		
02209	separator	rail mounting contactor separator	0.5	9 mm		
46392IPS	sheet of (48) marking tags (<i>mounts directly onto contactor</i>)					2232/4

19 series modular DIN rail mount relay (H) 84 x (W) 11.2 (D) 57 mm

- 3 function selector switch
 - Auto: Works as a monostable relay
 - OFF: Relay permanently OFF
 - ON: Relay permanently ON

- Slimline (*11.2 mm wide*) modular relay
- LED indication - auto-off-on selector

192100240000	10A	slimline	modular relay	1 ch/over	24V
--------------	-----	----------	---------------	-----------	-----