



Product designation

Illuminated button
actuators, spring
return - flush with
side visibility
8LM2TBL10

Product type designation

General characteristics

| | |
|--------------------------|--------------------------|
| Colour | Yellow |
| Material | Aluminium and zinc alloy |
| IEC degree of protection | IP65 |

Mechanical features

| | | |
|---|--------|-------------|
| Operating force | kg-lb | 0.8kg/1.7lb |
| Mechanical life - spring return actuators | cycles | 1000000 |
| Mounting adapter | | LM2TAU120 |
| Weight | g | 33 |

UL technical data

| | |
|-------------------------|-------------------------------|
| UL degree of protection | Type 1, 2, 3R, 4, 4X, 12, 12K |
|-------------------------|-------------------------------|

Ambient conditions

Temperature


Operating temperature

| | | |
|-----|----|-----|
| min | °C | -25 |
| max | °C | +60 |

Storage temperature

| | | |
|-----|----|-----|
| min | °C | -40 |
| max | °C | +70 |

Dimensions



Certifications and compliance

Compliance

CSA C22.2 n° 14
IEC/EN 60947-1
IEC/EN 60947-5-1
UL508

Certificates

CCC
cULus

EAC

LROS

RINA

ETIM classification

ETIM 8.0

EC000221 -
Front element for
push button