



Monoblock buzzer
- Continuous or pulse tone
LPCZS

Product designation

Product type designation

General characteristics

Material

Polyamide

IEC degree of protection

IP66, IP67;
IP96K on front
and IP20 on rear

Electrical characteristics

Rated impulse withstand voltage Uimp	kV	4
Rated frequency	Hz	50-60
Supply voltage (AC)	V	185...265
Supply voltage (DC)	V	185...265

Mechanical features

Tightening torque for terminals max	Nm	0.5
Screwdriver	Flat-head: 0.6x3.5mm/0.02x0.	
Conductor section		

AWG/kcmil conductor section

min	24
max	14

IEC

min	mm ²	0.5
max	mm ²	2.5

Weight g 20

UL technical data

UL degree of protection 1, 2, 3R, 4, 4X, 12, 12K on front

Ambient conditions

Temperature


Operating temperature

min	°C	-25
max	°C	+70


Storage temperature

min	°C	-40
max	°C	+85

Dimensions



Wiring diagrams



Certifications and compliance

Compliance

CSA C22.2 n° 14

IEC/EN/BS 60947-1

IEC/EN/BS 60947-5-1

UL508

Certificates

CCC

cULus

EAC

ETIM classification

ETIM 8.0

EC000130 -
 Signal horn