



We offer a selection of switching power supplies for DIN rail and screw mounting:

Typ	Mounting	Supply voltage	Output voltage	Rated current	Rated power	Efficiency	Dimensions (W x H x D)
DR-4624	DIN-Rail	85...264 V-AC, 47...63 Hz - 120...370 V-DC	21,6...26,4 V-DC	2 A	45 W	80 %	93 x 76 x 67 mm
DR-60-24	DIN-Rail	88...264 V-AC, 47...63 Hz - 124...370 V-DC	21,6...26,4 V-DC	2,5 A	60 W	84 %	78 x 93 x 56 mm
DR-75-24	DIN-Rail	85...264 V-AC, 47...63 Hz - 120...370 V-DC	24...28 V-DC	3,2 A	75 W	80 %	55 x 125,2 x 100 mm
DR-100-24	DIN-Rail	88...264 V-AC, 47...63 Hz - 124...370 V-DC	24...28 V-DC	4,2 A	100 W	88 %	100 x 93 x 56 mm
DR-120-24	DIN-Rail	88...120 V-AC / 176...264 V-AC (switch), 47...63 Hz - 246...370 V-DC	24...28 V-DC	5 A	120 W	84 %	65,5 x 125,2 x 100 mm
DRP-240-24	DIN-Rail	85...264 V-AC, 47...63 Hz - 120...370 V-DC	24...28 V-DC	10 A	240 W	84 %	125,5 x 125,2 x 100 mm
DRP-480-24	DIN-Rail	180...264 V-AC, 47...63 Hz - 250...370 V-DC	24...28 V-DC	20 A	480 W	89 %	227 x 125,2 x 100 mm
HLG-40H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22...27 V-DC	1,67 A	40 W	88 %	171 x 36,8 x 61,5 mm
HLG-60H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22...27 V-DC	2,5 A	60 W	89,5 %	171 x 36,8 x 61,5 mm
HLG-80H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22...27 V-DC	3,4 A	80 W	90,5 %	195,6 x 36,8 x 61,5 mm
HLG-100H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22...27 V-DC	4 A	100 W	93 %	220 x 36,8 x 68 mm
HLG-120H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22...27 V-DC	5 A	120 W	93 %	220 x 36,8 x 68 mm
HLG-150H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22...27 V-DC	6,3 A	150 W	93 %	228 x 36,8 x 68 mm
HLG-185H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22...27 V-DC	7,8 A	185 W	93,5 %	228 x 36,8 x 68 mm
HLG-240H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	22,4...25,6 V-DC	10 A	240 W	92,5 %	244,2 x 36,8 x 68 mm
HLG-320H-24	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	21...26 V-DC	13,3 A	320 W	94 %	252 x 43,8 x 90 mm
HLG-600H-24B	Screw mounting	90...305 V-AC, 47...63 Hz - 127...431 V-DC	20,4...25,2 V-DC	25 A	600 W	95 %	280 x 46,5 x 144 mm

Further types are available on request – please contact us!

Photos: Eimtron electronics GmbH